



Supply & Equipment

www.gunitesupply.com

Division of Mesa Industries, Inc.

Northeast
4141 Airport Rd.
Cincinnati, OH 45226
513.321.5526
888.321.5526

West
1726 S. Magnolia Ave.
Monrovia, CA 91016
626.358.0143
888.393.8635

Southeast
9202 Meadow Vista Blvd.
Houston, TX 77064
281.469.8097
800.258.2421

the **Mix-Elvator** Dry-Mix Guniting Batch Plant



Stop waiting for the ready-mix truck...take control of your next job!



- ★ Self-Contained Rig
- ★ Automatic Material Proportioning
- ★ Variable Ratio and Volume Control
- ★ All Hydraulic Gear, Pump and Motor
- ★ Continuous Feed
- ★ Easy to Operate and Maintain

Note: Performance is relative to material hose size, placement distance, available c.f.m. air and mix characteristics. Specifications subject to change.

Find us on the Web! www.gunitesupply.com



Supply & Equipment

www.gunitesupply.com

Division of Mesa Industries, Inc.

Buy direct from the source!



Applications

Pools & Spas
Refractories
Irrigation & Drainage Canals
Water Reservoirs & Basins
Parks & Zoos
Mines
Retaining & Fire Walls
Concrete Pipe
Columns & Beams
Curbs & Sidewalks
Bridges, Piers & Seawalls
Dams & Reservoirs
Sewers & Culverts
Brick & Old Concrete
Grain Bins & Silos
Loading Docks & Floors
Tunnels & Ditches
Flues & Chimneys
Furnaces, Ovens & Ladles
Residential Construction

The Mix-Elvator Delivers!

The Mix-Elvator is a medium to high production batch plant for continuous, automatic proportioning of dry gunite/concrete/refractory materials. It features a 30 hp diesel engine, low-maintenance hydraulic drive train and "Hydraulic-Ratio" control system. Combined with the C-10 gunite machine, the Mix-Elvator becomes a self-contained gunning rig for mixing and conveying material.

Specifications (Model 634 Mix-Elvator)

Max. Mixing Capacity

13 cu.yd. (9.9 cu.m.) (approx. 17 T)

Sand Hopper Capacity

20 cu.ft. (566L) Hopper is flared for Bobcat loading.

Cement Hopper Capacity

4 cu.ft. (113L)

Proportioning System

Exclusive "Hydraulic-Ratio" system

3:1, 5:1 or as required

Power Unit

30 hp diesel

Drive Train

All hydraulic with on-off / speed control and in-line filter system (Optional hydraulic circuit available when mounting gunite machine).

Trailer

Heavy-duty 5" steel channel frame, including retractable legs and jack; 2 ½ "I.D. towing eye; 6,000 lb. suspension axle; steel wheels; 700 x 15 – 8 ply tires; electric brakes and complete light package.

Dimensions

Length: 15'6" (472cm) Width: 7'3" (221cm)

Height: 7'2" (218cm) Weight: 4,300 lbs. (1,951kg)

Note: Performance is relative to material hose size, placement distance, available c.f.m. air and mix characteristics. Specifications subject to change.

